

INSTRUCTIONS / INVITATION FOR FORMAL BID PROPOSAL

An advertisement for sealed proposals to provide One(1)Conventional Chassis with Dump Body Per Specifications, Formal Bid #2010-003, for the City of Goldsboro and was published in the local newspaper in accordance with NC General Statutes on the 19th of March, 2010. As stated in such notice, proposals will be received until **10:00 a.m., local time on Thursday, April 8, 2010** and at that time, publicly opened and read aloud in the Large Conference Room located at 200 N. Center Street, Goldsboro, NC 27530.

The person, firm or corporation making a proposal shall submit it in a sealed envelope to the Finance Department on or before the hour and the day stated above. The words "**Formal Bid #2010-003 Per Specifications**" shall appear on the outside of the sealed envelope.

The Bidder shall insert the required responses and supply all the information, as requested, on the Bid Proposal Request Forms. The prices inserted shall be net and shall be the full cost, including all factors whatsoever. Any bids not submitted on such forms provided will be considered unresponsive.

No bid may be changed or withdrawn after the time of the bid opening. All modifications or withdrawals requested before this time shall be acceptable only when such request is made in writing to the Purchasing Agent.

The City of Goldsboro reserves the right to reject any and all bids, to waive all informalities and to accept the bid it deems most advantageous to the City. Any bid submitted will be binding for 60 days after the date of the bid opening.

Time of delivery to Goldsboro, NC will be a factor along with quality, cost, etc. in awarding the bids. Each proposal shall specify delivery time. Bids shall be FOB, Goldsboro, NC.

It is expressly understood by the bidders that written notice of award by the City will constitute an agreement by the City to consummate the transaction and will serve together with the proposal, the advertisement, these instructions and the detailed specifications, as the entire form of contract between the parties, except in cases where formal contracts are warranted.

The City incorporates into all specifications, purchase orders, and contracts that a vendor agrees not to discriminate against any employee or applicant for employment because of race, color, religion, sex, national origin or ancestry. By submitting a proposal, the firm is attesting that they are an Equal Opportunity Employer.

Federal law (Rehabilitation Act and ADA) prohibits handicapped discrimination by all governmental units. By submitting a proposal, the vendor is attesting to its policy of nondiscrimination regarding the handicapped.

Questions regarding any part of this bid shall be directed to the Finance Department,

P. O. Box Drawer A, Goldsboro, NC 27530, telephone (919) 580-4354 or Terry Cox may be contacted concerning technical questions on the Conventional Chassis with Dump Body to be bid at **(919) 739-7419**.

**The City of Goldsboro, North Carolina
PURCHASING OFFICE**

**One (1) Conventional Chassis with Dump Body
FORMAL BID #2010-003**

Pursuant to General Statutes of North Carolina, Section 160A-268, as amended, sealed bids and proposals are invited and, subject to the conditions on the reverse side hereof, will be received by the City of Goldsboro, in the Office of the Finance Department, City Hall, 200 N. Center Street, P. O. Drawer A, Goldsboro, N.C. 27534 until 10:00 am, on Thursday, April 8, 2010 at which time in a meeting in the Large Conference Room located in City Hall 200 N. Center Street the sealed bids and proposals will be publicly opened for furnishing the apparatus, supplies, materials, equipment and/or repair work and services, as described below.

THE CITY OF GOLDSBORO, N.C.

Bid Request No. FB 2010-003

Finance Department

By _____

ITEM NO.	QUANTIY	DESCRIPTION	UNIT PRICE
1.	1 ea.	Minimum Conventional Chassis with Dump Body Per Specifications <div style="text-align: center;"> Conventional Chassis Dump Body TOTAL </div>	
		*PLEASE FILL IN AMOUNT OF BID.	
		DEPOSIT: <u>WAIVED</u>	

POSITIVELY NO BIDS CONSIDERED UNLESS SUBMITTED ON THIS FORM

NOTICE TO BIDDERS: All tax imposed upon any article on which you are bidding shall be shown as separate items and in no case included with bid price. Failure to comply with these conditions will be considered grounds for rejection.

NAME: _____

ADDRESS: _____

TERMS: _____

TELEPHONE: _____

FAX: _____

EMAIL: _____

NOTE: BIDDERS, PLEASE FILL IN ABOVE

1. All bids and proposals shall be for furnishing apparatus, supplies, materials, equipment, and/or work and services in accordance with the applicable plans and specifications prescribed by The City of Goldsboro, from the date shown above until the date of opening the proposals, the plans and specifications of the proposed work and/or a complete description of the apparatus, supplies, materials, or equipment and/or work and services are and will continue to be filed in the Finance Department, at City Hall, 200 N. Center Street, P.O. Drawer A, Goldsboro, NC 27534 during usual office hours and available to prospective bidders.
2. The City reserves the right to reject any and all bids and proposals.
3. The bidder to whom contract is awarded must comply fully with the requirements of General Statutes, Section 143-129 as amended.
4. Time, in connection with discount offered, will be computed from the date of delivery of the supplies or materials to carrier when final inspection and acceptance are at point of origin, or from date of delivery at destination when final inspection and acceptance are at those points, or from date correct invoice is received if latter is later than the date of delivery.
5. In case of default of the contractor, the City may procure the articles or services from other sources and hold the contractor responsible for any excess cost occasioned thereby.
6. Payment by City due thirty days after delivery in Goldsboro and inspection unless otherwise specifically provided; subject to any discounts allowed.

BID _____ **Date** _____

In compliance with the above request for bids, and subject to all conditions thereof, the undersigned offers and agrees, if this bid be accepted within _____ Days from the date of the opening, to furnish any or all of the items upon which prices are quoted, at the price set opposite each item, and unless otherwise specified, within _____ Days after receipt of order, delivered

Discounts will be allowed for prompt payments as follows: 10 calendar days, _____ per cent; 15 calendar days, _____ per cent; 20 calendar days, _____ per cent; 30 calendar days, _____ per cent.

Bidder _____ Address _____

By _____ Title _____

ACCEPTANCE

Purchase Contract No. _____ Date _____

Accepted as to items numbered _____
 Authorized and accepted by City Council on _____ Day Of _____, _____.

THE CITY OF Goldsboro

BY _____
 Finance Director

INSTRUCTIONS TO BIDDERS

1. Samples of items, when required, must be furnished free of expense, prior to the opening of bids, and if not destroyed, will upon request, be returned at the bidders expense. Request for the return of samples must be made within 10 days, following opening of bids. Each individual sample must be labeled with bidder's name and item number.
2. Prices should be stated in units of quality specified with packing included.
3. If the item bid upon has a trade name or brand, such trade name or brand must be stated in the bid.
4. Attached complete specifications for any substitution offered, or when amplification is desirable or necessary.
5. If descriptive matter is attached to bid, bidders name must be on sheet containing descriptive matter.
6. Where a brand or trade name appears in the specifications it is understood that it refers to that material or its equivalent.
7. Please address and mark your bid as shown below.

Place Stamp Here
FINANCE DEPARTMENT P.O. DRAWER A 200 N. CENTER STREET GOLDSBORO, N.C. 27534
Bid # _____ Date of Bid _____



CITY OF GOLDSBORO, N.C.
GENERAL BID CONDITIONS
INFORMAL BID # FB 2010-003
CONVENTIONAL CHASSIS WITH DUMP BODY

- I. If the vehicle and equipment bid do not fully meet the specifications delineated in Specifications – Conventional Chassis with Dump Body of this Invitation to Bid, exceptions must be noted under the heading “Exceptions to Specifications” on a separate sheet attached to the Bid.

- II. The Bid **must** be accompanied by a complete set of specifications on vehicles and equipment proposed to be furnished.

- III. Earliest possible delivery is requested and the City of Goldsboro reserves the right to evaluate the delivery offered as a factor in determining award of this proposed contract. Therefore, please state your earliest guaranteed delivery after receipt of official purchase order in the appropriate space on the Bid Document.

- IV. The bidder to whom contract is awarded must comply fully with the requirements of North Carolina General Statutes, Section 143-129 as amended.

- V. The City of Goldsboro, NC reserves the right to reject any or all bids and to accept the bid which appears to be in the best interest of the City.

NOTE: If there are any obsolete items, please annotate that on your proposal and provide the City with the standard that is now used. If there are items that need clarification, please contact the Finance Department, Kaye Scott at (919)580-4354 or questions regarding specifications, contact Terry Cox at (919)739-7419.

S P E C I F I C A T I O N P R O P O S A L

Description	YES	NO	OFFERED
M2 106 CONVENTIONAL CHASSIS	_____	_____	_____
2011 MODEL YEAR SPECIFIED	_____	_____	_____
SET BACK AXLE - TRUCK	_____	_____	_____
STRAIGHT TRUCK PROVISION	_____	_____	_____
LH PRIMARY STEERING LOCATION	_____	_____	_____
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS	_____	_____	_____
MAXIMUM 8% EXPECTED GRADE	_____	_____	_____
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE	_____	_____	_____
MEDIUM TRUCK WARRANTY	_____	_____	_____
EXPECTED FRONT AXLE(S) LOAD : 14000.0 lbs	_____	_____	_____
EXPECTED REAR DRIVE AXLE(S) LOAD : 38000.0 lbs	_____	_____	_____
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 52000.0 lbs	_____	_____	_____
Truck Service			
END DUMP BODY	_____	_____	_____
EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0	_____	_____	_____
Engine			
EQUAL TO CUM ISC-270 270 HP @ 2000 RPM; 2200 GOV, 800 LB/FT @ 1300 RPM	_____	_____	_____
Electronic Parameters			
62 MPH ROAD SPEED LIMIT	_____	_____	_____
CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT	_____	_____	_____
PTO MODE ENGINE RPM LIMIT - 1100 RPM	_____	_____	_____
PTO RPM WITH CRUISE SET SWITCH - 800 RPM	_____	_____	_____
PTO RPM WITH CRUISE RESUME SWITCH - 700 RPM	_____	_____	_____
PTO MINIMUM RPM - 700	_____	_____	_____
REGEN INHIBITIT SPEED THRESHOLD - 5 MPH	_____	_____	_____
Engine Equipment			
2010 EPA/CARB EMISSION CERTIFICATION	_____	_____	_____
NO 2008 CARB EMISSION CERTIFICATION	_____	_____	_____
ENGINE MOUNTED OIL CHECK AND FILL	_____	_____	_____
ONE PIECE VALVE COVER	_____	_____	_____

Description	YES	NO	OFFERED
SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER			
Engine Equipment (continued)			
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE			
(2) ALLIANCE MODEL 1131, GROUP 31, 12 VOLT MAINTENANCE FREE 1850 CCA THREADED STUD BATTERIES			
BATTERY BOX FRAME MOUNTED			
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB			
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
NON-POLISHED BATTERY BOX COVER			
POSITIVE POST FOR JUMPSTART			
EQUAL TO CUMMINS 18.7 CFM COMPRESSOR WITH INTERNAL SAFETY VALVE			
AIR COMPRESSOR DISCHARGE LINE			
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO			
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE			
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH			
STANDARD EXHAUST SYSTEM LENGTH			
RH STANDARD HORIZONTAL TAILPIPE			
6 GALLON DIESEL EXHAUST FLUID TANK			
HORTON DRIVEMASTER ON/OFF FAN DRIVE OR EQUIVALENT			
AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED			
EQUAL TO CUMMINS SPIN ON FUEL FILTER			
COMBINATION FULL FLOW/BYPASS OIL FILTER			
1100 SQUARE INCH ALUMINUM RADIATOR			
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE-CHARGED SCA HEAVY DUTY COOLANT			
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES			
RADIATOR DRAIN VALVE			
LOWER RADIATOR GUARD			
ALUMINUM FLYWHEEL HOUSING			
ELECTRIC GRID AIR INTAKE WARMER			

Description	YES	NO	OFFERED
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH OR EQUAL			
Transmission			
ALLISON 3500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION OR EQUIVALENT			
Transmission Equipment			
WTEC CALIBRATION - 6 SPEED RDS WITH AUTO NEUTRAL (PACKAGE 170)			
CUSTOMER INSTALLED CHELSEA 230 SERIES PTO			
PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION			
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN			
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED			
TRANSMISSION PROGNOSTICS - DISABLED(N/A)			
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK			
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK			
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)			
Front Axle and Equipment			
MFS-14-143A 14,700# FF1 SINGLE FRONT AXLE OR EQUIVALENT			
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES OR EQUIVALENT			
NON-ASBESTOS FRONT BRAKE LINING OR EQUAL			
CONMET CAST IRON FRONT BRAKE DRUMS OR EQUAL			
CHICAGO RAWHIDE SCOTSEAL PLUS XL FRONT OIL SEALS OR EQUAL			
VENTED FRONT HUB CAPS - OIL			
STANDARD SPINDLE NUTS FOR ALL AXLES			
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS OR EQUAL			
TRW TAS-85 POWER STEERING OR EQUAL			
POWER STEERING PUMP			
2 QUART SEE THROUGH POWER STEERING RESERVOIR			
ORGANIC SAE 80/90 FRONT AXLE LUBE OR EQUIVALENT			

Description	YES	NO	OFFERED
Front Suspension			
16,000# TAPERLEAF FRONT SUSPENSION OR EQUIVALENT			
Front Suspension (continued)			
GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION OR EQUIVALENT			
FRONT SHOCK ABSORBERS			
Rear Axle and Equipment			
RT-40-145 40,000# R-SERIES TANDEM REAR AXLE			
6.14 REAR AXLE RATIO			
IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING			
17T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES			
17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES			
(1) INTERAXLE LOCK VALVE FOR TANDEM OR TRIDEM DRIVE AXLES			
BLINKING LAMP WITH EACH MODE SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF			
MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
NON-ASBESTOS REAR BRAKE LINING			
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)			
CONMET CAST IRON REAR BRAKE DRUMS			
CHICAGO RAWHIDE SCOTSEAL PLUS XL REAR OIL SEALS			
HALDEX GOLDSEAL LONGSTROKE 2-DRIVE AXLES SPRING PARKING CHAMBERS			
GUNITE AUTOMATIC REAR SLACK ADJUSTERS			
ORGANIC SAE 80/90 REAR AXLE LUBE			
Rear Suspension			
TUFTRAC 46,000# REAR SPRING SUSPENSION			
TUFTRAC STANDARD RIDE HEIGHT			
AXLE CLAMPING GROUP			
56 INCH AXLE SPACING			
FORE/AFT AND TRANSVERSE CONTROL RODS			
REAR SHOCK ABSORBERS - ONE AXLE			
Brake System			
AIR BRAKE PACKAGE			

Description	YES	NO	OFFERED
WABCO 4S/4M ABS WITHOUT TRACTION CONTROL			
REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
FIBER BRAID PARKING BRAKE HOSE			
Brake System (continued)			
STANDARD BRAKE SYSTEM VALVES			
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
WABCO SS-1200 PLUS AIR DRYER WITH INTEGRAL AIR GOVERNOR AND HEATER			
AIR DRYER FRAME MOUNTED			
STEEL AIR BRAKE RESERVOIRS			
STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM			
BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER - WET TANK			
Trailer Connections			
UPGRADED CHASSIS MULTIPLEXING UNIT			
UPGRADED BULKHEAD MULTIPLEXING UNIT			
Wheelbase & Frame			
5475MM (216 INCH) WHEELBASE			
7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI			
1900MM (75 INCH) REAR FRAME OVERHANG			
FRAME OVERHANG RANGE: 71 INCH TO 80 INCH			
SQUARE END OF FRAME			
FRONT CLOSING CROSSMEMBER			
LIGHT WEIGHT HEAVY DUTY ALUMINUM ENGINE CROSSMEMBER			
STANDARD MIDSHIP #1 CROSSMEMBER(S)			
STANDARD REARMOST CROSSMEMBER			
HEAVY DUTY SUSPENSION CROSSMEMBER			
Chassis Equipment			
THREE-PIECE 14 INCH PAINTED STEEL BUMPER WITH COLLAPSIBLE ENDS			
FRONT TOW HOOKS - FRAME MOUNTED			
BUMPER MOUNTING FOR SINGLE LICENSE PLATE			
NO MUDFLAP BRACKETS			
NO REAR MUDFLAPS			
CLEAR FRAME RAILS 36 INCHES FROM BACK OF CAB OUTBOARD OF BOTH FRAME RAILS			

Description	YES	NO	OFFERED
GRADE 8 THREADED HEX HEADED FRAME FASTENERS			
Fuel Tanks			
60 GALLON/227 LITER RECTANGULAR ALUMINUM FUEL TANK - LH			
Fuel Tanks (continued)			
RECTANGULAR FUEL TANK(S)			
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS			
FUEL TANK(S) FORWARD			
PLAIN STEP FINISH			
NO FUEL TANK SCREENS			
FUEL TANK CAP(S)			
ALLIANCE FUEL FILTER/WATER SEPARATOR			
EQUIFLO INBOARD FUEL SYSTEM			
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE			
Tires			
CONTINENTAL HSC 12R22.5 16 PLY RADIAL FRONT TIRES OR EQUIVALENT			
CONTINENTAL HDL ECO PLUS 11R22.5 14 PLY RADIAL REAR TIRES OR EQUIVALENT			
Hubs			
CONMET PRE-SET BEARING IRON FRONT HUBS OR EQUAL			
CONMET PRE-SET BEARING IRON REAR HUBS OR EQUAL			
Wheels			
ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS OR EQUAL			
HAYES LEMMERZ 90541 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC REAR WHEELS OR EQUAL			
Cab Exterior			
106 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB			
AIR CAB MOUNTS			
NO FENDER EXTENSION			
LH AND RH GRAB HANDLES			
PAINTED PLASTIC GRILLE			

Description	YES	NO	OFFERED
ARGENT SILVER HOOD MOUNTED AIR INTAKE GRILLE			
FIBERGLASS HOOD			
SINGLE 14 INCH ROUND POLISHED AIR HORN ROOF MOUNTED			
SINGLE ELECTRIC HORN			
SINGLE HORN SHIELD			
Cab Exterior (continued)			
DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
REAR LICENSE PLATE MOUNT END OF FRAME			
INTEGRAL HEADLIGHT/MARKER ASSEMBLY			
(5) AMBER MARKER LIGHTS			
INTEGRAL STOP/TAIL/BACKUP LIGHTS			
STANDARD FRONT TURN SIGNAL LAMPS			
DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE			
DOOR MOUNTED MIRRORS			
102 INCH EQUIPMENT WIDTH			
LH AND RH 8" BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS			
RH SURE PLUS 8 INCH BRIGHT FINISH FENDER MOUNTED CONVEX MIRROR WITH BRACKET			
STANDARD SIDE/REAR REFLECTORS			
NO CAB MOUNTED STEPS			
63X14 INCH TINTED REAR WINDOW			
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS			
MANUAL DOOR WINDOW REGULATORS			
TINTED WINDSHIELD			
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED			
Cab Interior			
OPAL GRAY VINYL INTERIOR			
MOLDED PLASTIC DOOR PANEL WITH ALUMINUM KICKPLATE LOWER DOOR			
MOLDED PLASTIC DOOR PANEL			
GRAY VINYL MATS WITH INSULATION			
NO DASH MOUNTED ASH TRAYS AND LIGHTER			
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING			
IN DASH STORAGE BIN			

Description	YES	NO	OFFERED
(2) CUP HOLDERS LH AND RH DASH			
GRAY/CHARCOAL FLAT DASH			
2-1/2 LB. FIRE EXTINGUISHER			
HEATER, DEFROSTER AND AIR CONDITIONER			
STANDARD HVAC DUCTING			
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH			
STANDARD HEATER PLUMBING			
Cab Interior (continued)			
SANDEN HEAVY DUTY AIR CONDITIONER COMPRESSOR			
BINARY CONTROL, R-134A			
CAB INSULATION			
SOLID-STATE CIRCUIT PROTECTION AND FUSES			
12V NEGATIVE GROUND ELECTRICAL SYSTEM			
DOME LIGHT WITH 3-WAY SWITCH ACTIVATED BY LH AND RH DOORS			
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS			
TRIANGULAR REFLECTORS WITHOUT FLARES			
BOSTROM TALLADEGA 910 HIGH BACK AIR SUSPENSION DRIVER SEAT			
2 MAN TOOL BOX MID BACK NON SUSPENSION PASSENGER SEAT			
LH AND RH INTEGRAL DOOR PANEL ARMRESTS			
VINYL WITH VINYL INSERT DRIVER SEAT			
VINYL WITH VINYL INSERT PASSENGER SEAT			
3 POINT DRIVER AND PASSENGER AND 2 POINT CENTER FRONT SEAT BELT RETRACTORS			
ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN			
4-SPOKE 18 INCH (450MM) STEERING WHEEL			
DRIVER AND PASSENGER INTERIOR SUN VISORS			
Instruments & Controls			
BLACK GAUGE BEZELS			
GRAY DRIVER INSTRUMENT PANEL			
GRAY CENTER INSTRUMENT PANEL			
LOW AIR PRESSURE LIGHT AND BUZZER			
2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES			
INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS			

Description	YES	NO	OFFERED
ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL			
KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			
ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3			
DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH			
2 INCH ELECTRIC FUEL GAUGE			
Instruments & Controls (continued)			
PROGRAMMABLE RPM CONTROL - ELECTRONIC ENGINE			
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			
TRANSMISSION OIL TEMPERATURE INDICATOR LIGHT			
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
ELECTRIC ENGINE OIL PRESSURE GAUGE			
AM/FM/WB RADIO WITH FRONT AUXILIARY INPUT			
DASH MOUNTED RADIO			
(2) RADIO SPEAKERS IN CAB			
AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF			
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			
ELECTRONIC 3000 RPM TACHOMETER			
IDLE LIMITER, ELECTRONIC ENGINE			
TWO EXTRA SWITCHES IN DASH WITH INDICATOR LAMP AND WIRE TO CHASSIS AT BACK OF CAB/SLEEPER			
NO TRAILER HAND CONTROL BRAKE VALVE			
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY			
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH			
CONTROL & PIPING-PARK BRK, CAB			
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE			

Description	YES	NO	OFFERED
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS			
Design			
PAINT: ONE SOLID COLOR			
Color			
CAB COLOR A: WHITE			
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT			
VENDOR WHITE FRONT WHEELS/RIMS			
VENDOR WHITE REAR WHEELS/RIMS			
BUMPER PAINT: SILVER			

BODY SPECIFICATIONS

Description	YES	NO	OFFERED
16 FT. BODY W/ 48" SIDES OR EQUIVALENT			
1/2 " CAB SHIELD			
ASPHALT LIP			
HORIZONTAL BRACING			
AIR BARNDOOR W/AIR TAILGATE OR EQUAL			
HOIST			
8" BOARDS			
ELECTRIC TARP SYSTEM			
PAINT: BLACK			
MUDFLAPS			
BACK-UP ALARM			
CONSOLE CONTROL			